


HALOGEN FLASHERS

Halogen Flashers

A range of solid state & relay based halogen flashers designed specifically for the Emergency Services for head light flashing. SSF & HF Series have simultaneous/alternating outputs with night time inhibit facility.



SSFPOS-UK
SOLID-STATE

FEATURES:


- 100% Solid-State flasher with encapsulated electronics.
- For Positive switching headlights.
- 2 outlet, 160watt per outlet.
- 12.8 VDC, 12.5 amps output.
- High beam override & night time inhibit.
- Scan-Lock provides seven flash patterns which can be accessed by a momentary switch.


FLASH PATTERNS:

Composite 75 Single Flash Alternating/75 Single Flash Simultaneous.
 75 Single Flash Alternating.
 75 Single Flash Simultaneous.
 280 Single Flash Alternating.
 Composite 140 Double Flash Alternating/140 Single Flash Simultaneous.
 Composite 140 Double Flash Alternating/280 Single Flash Simultaneous.

10-16
VDC

e11
✓





2
YEAR
WARRANTY

Dimensions (mm): H22 X W51 X L70

EL12W/EL13W - SINGLE RELAY



Flasher relay unit with sealed electronics and alternating output pair. 10 amps maximum per outlet.

70 flashes per minute per outlet.

Dimensions (mm): H22 X W51 X L70

12
VDC


24
VDC

Model EL13H as EL13W but with fog light interface (12VDC only).

e11
✓

1
YEAR
WARRANTY

HF1000/HF1001 - DUAL RELAY



HF1000/HF1001 provides two alternating or simultaneous positive outputs to flash the vehicle headlights. Night time inhibit.

70 flashes per minute per outlet.

Dimensions (mm): H32 X W132 X L64

12
VDC

24
VDC

e11
✓

1
YEAR
WARRANTY



WOODWAY®
Woodway Engineering Limited

